


TABLE 2B

Wedge Section:SPB



Top Width: 17.0 mm; Thickness: 14.0 mm; Angle: 40°
Standard: IS 14261, BS 3790, ISO 4184, DIN 7753
Temperature Range: + 70°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
SPB1250	1190	1250	SPB2400	2340	2400	SPB4060	4000	4060
SPB1260	1200	1260	SPB2410	2350	2410	SPB4250	4190	4250
SPB1320	1260	1320	SPB2500	2440	2500	SPB4310	4250	4310
SPB1340	1280	1340	SPB2530	2470	2530	SPB4500	4440	4500
SPB1400	1340	1400	SPB2600	2540	2600	SPB4560	4500	4560
SPB1410	1350	1410	SPB2650	2590	2650	SPB4750	4690	4750
SPB1500	1440	1500	SPB2680	2620	2680	SPB4820	4760	4820
SPB1550	1490	1550	SPB2700	2640	2700	SPB5000	4940	5000
SPB1600	1540	1600	SPB2750	2690	2750	SPB5070	5010	5070
SPB1700	1640	1700	SPB2800	2740	2800	SPB5300	5240	5300
SPB1750	1690	1750	SPB2840	2780	2840	SPB5380	5320	5380
SPB1800	1740	1800	SPB2900	2840	2900	SPB5600	5540	5600
SPB1900	1840	1900	SPB3000	2940	3000	SPB5880	5820	5880
SPB2000	1940	2000	SPB3100	3040	3100	SPB6000	5940	6000
SPB2020	1960	2020	SPB3150	3090	3150	SPB6300	6240	6300
SPB2060	2000	2060	SPB3170	3110	3170	SPB6340	6280	6340
SPB2120	2060	2120	SPB3350	3290	3350	SPB6700	6640	6700
SPB2150	2090	2150	SPB3550	3490	3550	SPB7100	7040	7100
SPB2240	2180	2240	SPB3750	3690	3750	SPB7500	7440	7500
SPB2280	2220	2280	SPB3800	3740	3800	SPB8000	7940	8000
SPB2360	2300	2360	SPB4000	3940	4000			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request