


# ENDURA HI-TECH 'FLEX' COGGED V BELTS

**TABLE 4A**

**Classical Section:AX**




**Top Width:** 13.0 mm; **Thickness:** 8.0 mm; **Angle:** 36°  
**Standard:** IS 2494, BS 3790, ISO 4184, IP20  
**Ambient Temperature Range:** + 90°C to -18°C  
**Features:** Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
AX26	660	696	AX38	965	1001	AX50	1270	1306	AX62	1575	1611	AX74	1880	1916
AX27	686	722	AX39	991	1027	AX51	1295	1331	AX63	1600	1636	AX75	1905	1941
AX28	711	747	AX40	1016	1052	AX52	1321	1357	AX64	1626	1662	AX76	1930	1966
AX29	737	773	AX41	1041	1077	AX53	1346	1382	AX65	1651	1687	AX77	1956	1992
AX30	762	798	AX42	1067	1103	AX54	1372	1408	AX66	1676	1712	AX78	1981	2017
AX31	787	823	AX43	1092	1128	AX55	1397	1433	AX67	1702	1738	AX79	2007	2043
AX32	813	849	AX44	1118	1154	AX56	1422	1458	AX68	1727	1763	AX80	2032	2068
AX33	838	874	AX45	1143	1179	AX57	1448	1484	AX69	1753	1789	AX82	2083	2119
AX34	864	900	AX46	1168	1204	AX58	1473	1509	AX70	1778	1814	AX83	2108	2144
AX35	889	925	AX47	1194	1230	AX59	1499	1535	AX71	1803	1839	AX84	2134	2170
AX36	914	950	AX48	1219	1255	AX60	1524	1560	AX72	1829	1865	AX85	2159	2195
AX37	940	976	AX49	1245	1281	AX61	1549	1585	AX73	1854	1890			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request  
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request

**TABLE 4B**

**Classical Section:BX**



**Top Width:** 17.0 mm; **Thickness:** 11.0 mm; **Angle:** 36°  
**Standard:** IS 2494, BS 3790, ISO 4184, IP20  
**Ambient Temperature Range:** + 90°C to -18°C  
**Features:** Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
BX26	660	703	BX41	1041	1084	BX55	1397	1440	BX69	1753	1796	BX83	2108	2151
BX28	711	754	BX42	1067	1110	BX56	1422	1465	BX70	1778	1821	BX84	2134	2177
BX29	737	780	BX43	1092	1135	BX57	1448	1491	BX71	1803	1846	BX85	2159	2202
BX30	762	805	BX44	1118	1161	BX58	1473	1516	BX72	1829	1872	BX86	2184	2227
BX31	787	830	BX45	1143	1186	BX59	1499	1542	BX73	1854	1897	BX87	2210	2253
BX32	813	856	BX46	1168	1211	BX60	1524	1567	BX74	1880	1923	BX88	2235	2278
BX33	838	881	BX47	1194	1237	BX61	1549	1592	BX75	1905	1948	BX89	2261	2304
BX34	864	907	BX48	1219	1262	BX62	1575	1618	BX76	1930	1973	BX90	2286	2329
BX35	889	932	BX49	1245	1288	BX63	1600	1643	BX77	1956	1999	BX95	2413	2456
BX36	914	957	BX50	1270	1313	BX64	1626	1669	BX78	1981	2024	BX100	2540	2583
BX37	940	983	BX51	1295	1338	BX65	1651	1694	BX79	2007	2050	BX105	2667	2710
BX38	965	1008	BX52	1321	1364	BX66	1676	1719	BX80	2032	2075	BX110	2794	2837
BX39	991	1034	BX53	1346	1389	BX67	1702	1745	BX81	2057	2100	BX120	3048	3091
BX40	1016	1059	BX54	1372	1415	BX68	1727	1770	BX82	2083	2126			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request  
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request