


ENDURA HI-TECH 'CORE' CLASSICAL V BELTS

TABLE 1A

Classical Section:A



Top Width: 13.0 mm; **Thickness:** 8.0 mm; **Angle:** 40°
Standard: IS2494,BS3790, ISO4184, DIN2215,JIS K 6323, IP 20
Ambient Temperature Range: + 70°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
A19	483	519	A55	1397	1433	A91	2311	2347	A140	3556	3592
A20	508	544	A56	1422	1458	A92	2337	2373	A144	3658	3694
A21	533	569	A57	1448	1484	A93	2362	2398	A146	3708	3744
A22	559	595	A58	1473	1509	A94	2388	2424	A150	3810	3846
A23	584	620	A59	1499	1535	A95	2413	2449	A152	3861	3897
A24	610	646	A60	1524	1560	A96	2438	2474	A156	3962	3998
A25	635	671	A61	1549	1585	A97	2464	2500	A158	4013	4049
A26	660	696	A62	1575	1611	A98	2489	2525	A160	4064	4100
A27	686	722	A63	1600	1636	A99	2515	2551	A165	4191	4227
A28	711	747	A64	1626	1662	A100	2540	2576	A168	4267	4303
A29	737	773	A65	1651	1687	A101	2565	2601	A170	4318	4354
A30	762	798	A66	1676	1712	A102	2591	2627	A172	4369	4405
A31	787	823	A67	1702	1738	A103	2616	2652	A173	4394	4430
A32	813	849	A68	1727	1763	A104	2642	2678	A175	4445	4481
A33	838	874	A69	1753	1789	A105	2667	2703	A178	4521	4557
A34	864	900	A70	1778	1814	A106	2692	2728	A180	4572	4608
A35	889	925	A71	1803	1839	A107	2718	2754	A182	4623	4659
A36	914	950	A72	1829	1865	A108	2743	2779	A185	4699	4735
A37	940	976	A73	1854	1890	A110	2794	2830	A190	4826	4862
A38	965	1001	A74	1880	1916	A112	2845	2881	A192	4877	4913
A39	991	1027	A75	1905	1941	A113	2870	2906	A195	4953	4989
A40	1016	1052	A76	1930	1966	A114	2896	2932	A200	5080	5116
A41	1041	1077	A77	1956	1992	A115	2921	2957	A205	5207	5243
A42	1067	1103	A78	1981	2017	A116	2946	2982			
A43	1092	1128	A79	2007	2043	A118	2997	3033			
A44	1118	1154	A80	2032	2068	A120	3048	3084			
A45	1143	1179	A81	2057	2093	A122	3099	3135			
A46	1168	1204	A82	2083	2119	A124	3150	3186			
A47	1194	1230	A83	2108	2144	A125	3175	3211			
A48	1219	1255	A84	2134	2170	A126	3200	3236			
A49	1245	1281	A85	2159	2195	A128	3251	3287			
A50	1270	1306	A86	2184	2220	A130	3302	3338			
A51	1295	1331	A87	2210	2246	A132	3353	3389			
A52	1321	1357	A88	2235	2271	A134	3404	3440			
A53	1346	1382	A89	2261	2297	A136	3454	3490			
A54	1372	1408	A90	2286	2322	A138	3505	3541			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request