


TABLE 1B

Classical Section:B



Top Width: 17.0 mm; Thickness: 11.0 mm; Angle: 40°
Standard: IS2494,BS3790,ISO4184, DIN2215,JIS K 6323, IP 20
Ambient Temperature Range: + 70°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
B22	559	602	B58	1473	1516	B94	2388	2431	B130	3302	3345	B190	4826	4869
B23	584	627	B59	1499	1542	B95	2413	2456	B132	3353	3396	B195	4953	4996
B24	610	653	B60	1524	1567	B96	2438	2481	B134	3404	3447	B200	5080	5123
B25	635	678	B61	1549	1592	B97	2464	2507	B135	3429	3472	B204	5182	5225
B26	660	703	B62	1575	1618	B98	2489	2532	B136	3454	3497	B205	5207	5250
B27	686	729	B63	1600	1643	B99	2515	2558	B138	3505	3548	B210	5334	5377
B28	711	754	B64	1626	1669	B100	2540	2583	B140	3556	3599	B225	5715	5758
B29	737	780	B65	1651	1694	B101	2565	2608	B142	3607	3650	B238	6045	6088
B30	762	805	B66	1676	1719	B102	2591	2634	B144	3658	3701	B250	6350	6393
B31	787	830	B67	1702	1745	B103	2616	2659	B145	3683	3726	B260	6604	6647
B32	813	856	B68	1727	1770	B104	2642	2685	B146	3708	3751	B275	6985	7028
B33	838	881	B69	1753	1796	B105	2667	2710	B148	3759	3802	B300	7620	7663
B34	864	907	B70	1778	1821	B106	2692	2735	B150	3810	3853	B310	7874	7917
B35	889	932	B71	1803	1846	B107	2718	2761	B152	3861	3904	B440	11176	11219
B36	914	957	B72	1829	1872	B108	2743	2786	B154	3912	3955			
B37	940	983	B73	1854	1897	B109	2769	2812	B155	3937	3980			
B38	965	1008	B74	1880	1923	B110	2794	2837	B156	3962	4005			
B39	991	1034	B75	1905	1948	B111	2819	2862	B158	4013	4056			
B40	1016	1059	B76	1930	1973	B112	2845	2888	B160	4064	4107			
B41	1041	1084	B77	1956	1999	B113	2870	2913	B162	4115	4158			
B42	1067	1110	B78	1981	2024	B114	2896	2939	B164	4166	4209			
B43	1092	1135	B79	2007	2050	B115	2921	2964	B165	4191	4234			
B44	1118	1161	B80	2032	2075	B116	2946	2989	B166	4216	4259			
B45	1143	1186	B81	2057	2100	B117	2972	3015	B168	4267	4310			
B46	1168	1211	B82	2083	2126	B118	2997	3040	B169	4293	4336			
B47	1194	1237	B83	2108	2151	B119	3023	3066	B170	4318	4361			
B48	1219	1262	B84	2134	2177	B120	3048	3091	B172	4369	4412			
B49	1245	1288	B85	2159	2202	B121	3073	3116	B173	4394	4437			
B50	1270	1313	B86	2184	2227	B122	3099	3142	B175	4445	4488			
B51	1295	1338	B87	2210	2253	B123	3124	3167	B176	4470	4513			
B52	1321	1364	B88	2235	2278	B124	3150	3193	B178	4521	4564			
B53	1346	1389	B89	2261	2304	B125	3175	3218	B180	4572	4615			
B54	1372	1415	B90	2286	2329	B126	3200	3243	B182	4623	4666			
B55	1397	1440	B91	2311	2354	B127	3226	3269	B184	4674	4717			
B56	1422	1465	B92	2337	2380	B128	3251	3294	B185	4699	4742			
B57	1448	1491	B93	2362	2405	B129	3277	3320	B188	4775	4818			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request