


TABLE 1D

Classical Section:D




Top Width: 32.0 mm; Thickness: 19.0 mm; Angle: 40°
Standard: IS2494,BS3790, ISO4184, DIN2215,JIS K 6323, IP 20
Ambient Temperature Range: + 70°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
D75	1905	1984	D116	2946	3025	D168	4267	4346	D248	6299	6378	D478	12141	12220
D80	2032	2111	D120	3048	3127	D173	4394	4473	D250	6350	6429	D538	13665	13744
D82	2083	2162	D122	3099	3178	D175	4445	4524	D258	6553	6632			
D84	2134	2213	D128	3251	3330	D180	4572	4651	D260	6604	6683			
D85	2159	2238	D130	3302	3381	D185	4699	4778	D268	6807	6886			
D88	2235	2314	D132	3353	3432	D190	4826	4905	D280	7112	7191			
D90	2286	2365	D134	3404	3483	D195	4953	5032	D285	7239	7318			
D95	2413	2492	D136	3454	3533	D204	5182	5261	D290	7366	7445			
D96	2438	2517	D138	3505	3584	D210	5334	5413	D298	7569	7648			
D98	2489	2568	D140	3556	3635	D215	5461	5540	D300	7620	7699			
D100	2540	2619	D144	3658	3737	D220	5588	5667	D314	7976	8055			
D102	2591	2670	D150	3810	3889	D225	5715	5794	D320	8128	8207			
D105	2667	2746	D152	3861	3940	D228	5791	5870	D328	8331	8410			
D108	2743	2822	D158	4013	4092	D230	5842	5921	D358	9093	9172			
D110	2794	2873	D160	4064	4143	D238	6045	6124	D390	9906	9985			
D112	2845	2924	D162	4115	4194	D240	6096	6175	D418	10617	10696			
D114	2896	2975	D165	4191	4270	D245	6223	6302	D450	11430	11509			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request

TABLE 1E

Classical Section:E



Top Width: 38.0 mm; Thickness: 23.0 mm; Angle: 40°
Standard: IS 2494, ISO 4184, JISK6323,IP20
Ambient Temperature Range: + 70°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
E180	4572	4664	E268	6807	6899	E374	9500	9592	E478	12141	12233
E195	4953	5045	E298	7569	7661	E394	10008	10100	E538	13665	13757
E210	5334	5426	E328	8331	8423	E418	10617	10709			
E238	6045	6137	E358	9093	9185	E450	11430	11522			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request