


TABLE 1C

Classical Section:C



Top Width: 22.0 mm; Thickness: 14.0 mm; Angle: 40°
Standard: IS2494,BS3790, ISO4184, DIN2215,JIS K 6323, IP 20
Ambient Temperature Range: + 70°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
C36	914	970	C72	1829	1885	C108	2743	2799	C146	3708	3764	C218	5537	5593
C37	940	996	C73	1854	1910	C109	2769	2825	C148	3759	3815	C220	5588	5644
C38	965	1021	C74	1880	1936	C110	2794	2850	C150	3810	3866	C225	5715	5771
C39	991	1047	C75	1905	1961	C111	2819	2875	C152	3861	3917	C228	5791	5847
C40	1016	1072	C76	1930	1986	C112	2845	2901	C154	3912	3968	C230	5842	5898
C41	1041	1097	C77	1956	2012	C113	2870	2926	C155	3937	3993	C235	5969	6025
C42	1067	1123	C78	1981	2037	C114	2896	2952	C156	3962	4018	C238	6045	6101
C43	1092	1148	C79	2007	2063	C115	2921	2977	C158	4013	4069	C240	6096	6152
C44	1118	1174	C80	2032	2088	C116	2946	3002	C160	4064	4120	C245	6223	6279
C45	1143	1199	C81	2057	2113	C117	2972	3028	C162	4115	4171	C248	6299	6355
C46	1168	1224	C82	2083	2139	C118	2997	3053	C164	4166	4222	C250	6350	6406
C47	1194	1250	C83	2108	2164	C119	3023	3079	C165	4191	4247	C255	6477	6533
C48	1219	1275	C84	2134	2190	C120	3048	3104	C166	4216	4272	C260	6604	6660
C49	1245	1301	C85	2159	2215	C121	3073	3129	C168	4267	4323	C268	6807	6863
C50	1270	1326	C86	2184	2240	C122	3099	3155	C169	4293	4349	C270	6858	6914
C51	1295	1351	C87	2210	2266	C123	3124	3180	C170	4318	4374	C275	6985	7041
C52	1321	1377	C88	2235	2291	C124	3150	3206	C172	4369	4425	C280	7112	7168
C53	1346	1402	C89	2261	2317	C125	3175	3231	C173	4394	4450	C285	7239	7295
C54	1372	1428	C90	2286	2342	C126	3200	3256	C174	4420	4476	C290	7366	7422
C55	1397	1453	C91	2311	2367	C127	3226	3282	C175	4445	4501	C300	7620	7676
C56	1422	1478	C92	2337	2393	C128	3251	3307	C178	4521	4577	C328	8331	8387
C57	1448	1504	C93	2362	2418	C130	3302	3358	C180	4572	4628	C358	9093	9149
C58	1473	1529	C94	2388	2444	C131	3327	3383	C182	4623	4679	C418	10617	10673
C59	1499	1555	C95	2413	2469	C132	3353	3409	C184	4674	4730			
C60	1524	1580	C96	2438	2494	C133	3378	3434	C185	4699	4755			
C61	1549	1605	C97	2464	2520	C134	3404	3460	C188	4775	4831			
C62	1575	1631	C98	2489	2545	C135	3429	3485	C190	4826	4882			
C63	1600	1656	C99	2515	2571	C136	3454	3510	C192	4877	4933			
C64	1626	1682	C100	2540	2596	C137	3480	3536	C195	4953	5009			
C65	1651	1707	C101	2565	2621	C138	3505	3561	C198	5029	5085			
C66	1676	1732	C102	2591	2647	C139	3531	3587	C200	5080	5136			
C67	1702	1758	C103	2616	2672	C140	3556	3612	C204	5182	5238			
C68	1727	1783	C104	2642	2698	C141	3581	3637	C205	5207	5263			
C69	1753	1809	C105	2667	2723	C142	3607	3663	C208	5283	5339			
C70	1778	1834	C106	2692	2748	C144	3658	3714	C210	5334	5390			
C71	1803	1859	C107	2718	2774	C145	3683	3739	C215	5461	5517			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request