


ENDURA HI-TECH 'CORE' WEDGE V BELTS

TABLE 2A

Wedge Section: SPA



Top Width: 13.0 mm; **Thickness:** 10.0 mm; **Angle:** 40°

Standard: IS 14261, BS 3790, ISO 4184, DIN 7753

Temperature Range: + 70°C to -18°C

Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
SPA800	755	800	SPA1320	1275	1320	SPA2180	2135	2180
SPA825	780	825	SPA1340	1295	1340	SPA2200	2155	2200
SPA850	805	850	SPA1360	1315	1360	SPA2240	2195	2240
SPA875	830	875	SPA1400	1355	1400	SPA2280	2235	2280
SPA900	855	900	SPA1437	1392	1437	SPA2300	2255	2300
SPA925	880	925	SPA1450	1405	1450	SPA2360	2315	2360
SPA950	905	950	SPA1475	1430	1475	SPA2430	2385	2430
SPA975	930	975	SPA1500	1455	1500	SPA2500	2455	2500
SPA1000	955	1000	SPA1550	1505	1550	SPA2580	2535	2580
SPA1030	985	1030	SPA1600	1555	1600	SPA2650	2605	2650
SPA1060	1015	1060	SPA1650	1605	1650	SPA2720	2675	2720
SPA1080	1035	1080	SPA1700	1655	1700	SPA2800	2755	2800
SPA1090	1045	1090	SPA1750	1705	1750	SPA2900	2855	2900
SPA1100	1055	1100	SPA1800	1755	1800	SPA3000	2955	3000
SPA1120	1075	1120	SPA1850	1805	1850	SPA3150	3105	3150
SPA1150	1105	1150	SPA1900	1855	1900	SPA3350	3305	3350
SPA1180	1135	1180	SPA1925	1880	1925	SPA3550	3505	3550
SPA1200	1155	1200	SPA1950	1905	1950	SPA3750	3705	3750
SPA1220	1175	1220	SPA2000	1955	2000	SPA4000	3955	4000
SPA1250	1205	1250	SPA2057	2012	2057	SPA4250	4205	4250
SPA1280	1235	1280	SPA2060	2015	2060	SPA4500	4455	4500
SPA1300	1255	1300	SPA2120	2075	2120			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request