


TABLE 2C

Wedge Section:SPC




Top Width: 22.0 mm; **Thickness:** 18.0 mm; **Angle:** 40°
Standard: IS 14261, BS 3790, ISO 4184, DIN 7753
Temperature Range: + 70°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
SPC2000	1917	2000	SPC3350	3267	3350	SPC5300	5217	5300	SPC8500	8417	8500
SPC2120	2037	2120	SPC3550	3467	3550	SPC5480	5397	5480	SPC9000	8917	9000
SPC2240	2157	2240	SPC3600	3517	3600	SPC5600	5517	5600	SPC9500	9417	9500
SPC2360	2277	2360	SPC3750	3667	3750	SPC6000	5917	6000	SPC10000	9917	10000
SPC2500	2417	2500	SPC4000	3917	4000	SPC6300	6217	6300	SPC10600	10517	10600
SPC2650	2567	2650	SPC4250	4167	4250	SPC6700	6617	6700	SPC11200	11117	11200
SPC2800	2717	2800	SPC4500	4417	4500	SPC7100	7017	7100	SPC11800	11717	11800
SPC3000	2917	3000	SPC4750	4667	4750	SPC7500	7417	7500	SPC12500	12417	12500
SPC3150	3067	3150	SPC5000	4917	5000	SPC8000	7917	8000			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request

TABLE 2D

Wedge Section:SPZ



Top Width: 10.0 mm; **Thickness:** 8.0 mm; **Angle:** 40°
Standard: IS 14261, BS 3790, ISO 4184, DIN 7753
Temperature Range: + 70°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
SPZ630	593	630	SPZ1140	1103	1140	SPZ1450	1413	1450	SPZ2100	2063	2100
SPZ670	633	670	SPZ1170	1133	1170	SPZ1470	1433	1470	SPZ2120	2083	2120
SPZ710	673	710	SPZ1180	1143	1180	SPZ1500	1463	1500	SPZ2160	2123	2160
SPZ750	713	750	SPZ1200	1163	1200	SPZ1520	1483	1520	SPZ2240	2203	2240
SPZ760	723	760	SPZ1220	1183	1220	SPZ1560	1523	1560	SPZ2280	2243	2280
SPZ800	763	800	SPZ1250	1213	1250	SPZ1600	1563	1600	SPZ2410	2373	2410
SPZ825	788	825	SPZ1270	1233	1270	SPZ1650	1613	1650	SPZ2500	2463	2500
SPZ850	813	850	SPZ1300	1263	1300	SPZ1700	1663	1700	SPZ2540	2503	2540
SPZ900	863	900	SPZ1320	1283	1320	SPZ1720	1683	1720	SPZ2650	2613	2650
SPZ940	903	940	SPZ1340	1303	1340	SPZ1737	1700	1737	SPZ2680	2643	2680
SPZ1000	963	1000	SPZ1348	1311	1348	SPZ1787	1750	1787	SPZ2800	2763	2800
SPZ1010	973	1010	SPZ1358	1321	1358	SPZ1800	1763	1800	SPZ2840	2803	2840
SPZ1050	1013	1050	SPZ1375	1338	1375	SPZ1850	1813	1850	SPZ3000	2963	3000
SPZ1080	1043	1080	SPZ1400	1363	1400	SPZ1900	1863	1900			
SPZ1100	1063	1100	SPZ1420	1383	1420	SPZ2000	1963	2000			
SPZ1120	1083	1120	SPZ1440	1403	1440	SPZ2030	1993	2030			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request