


ENDURA HI-TECH 'CORE' NARROW V BELTS

TABLE 3A

Narrow Section: 3V




Top Width: 10.0 mm; **Thickness:** 8.0 mm; **Angle:** 40°
Standard: RMA IP 22
Temperature Range: + 70°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Outside Length	Belt Code	Inside Length	Outside Length	Belt Code	Inside Length	Outside Length
3V450	1093	1143	3V670	1652	1702	3V900	2236	2286
3V480	1169	1219	3V710	1753	1803	3V950	2363	2413
3V500	1220	1270	3V750	1855	1905	3V1000	2490	2540
3V530	1296	1346	3V770	1906	1956	3V1060	2642	2692
3V560	1372	1422	3V780	1931	1981	3V1120	2795	2845
3V600	1474	1524	3V790	1957	2007	3V1180	2947	2997
3V630	1550	1600	3V800	1982	2032			
3V650	1601	1651	3V850	2109	2159			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request

TABLE 3B

Narrow Section: 5V



Top Width: 16.0 mm; **Thickness:** 14.0 mm; **Angle:** 40°
Standard: RMA IP 22
Temperature Range: + 70°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Outside Length	Belt Code	Inside Length	Outside Length	Belt Code	Inside Length	Outside Length
5V480	1134	1219	5V1000	2455	2540	5V1900	4741	4826
5V500	1185	1270	5V1060	2607	2692	5V2000	4995	5080
5V530	1261	1346	5V1120	2760	2845	5V2120	5300	5385
5V600	1439	1524	5V1180	2912	2997	5V2240	5605	5690
5V630	1515	1600	5V1250	3090	3175	5V2360	5909	5994
5V710	1718	1803	5V1320	3268	3353	5V2500	6265	6350
5V750	1820	1905	5V1400	3471	3556	5V2650	6646	6731
5V800	1947	2032	5V1500	3725	3810	5V2800	7027	7112
5V850	2074	2159	5V1600	3979	4064	5V3000	7535	7620
5V900	2201	2286	5V1700	4233	4318			
5V950	2328	2413	5V1800	4487	4572			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request