


TABLE 4C

Classical Section: CX



Top Width: 22.0 mm; **Thickness:** 14.0 mm; **Angle:** 36°
Standard: IS 2494, BS 3790, ISO 4184, IP20
Ambient Temperature Range: + 90°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
CX38	965	1021	CX62	1575	1631	CX86	2184	2240
CX40	1016	1072	CX64	1626	1682	CX88	2235	2291
CX42	1067	1123	CX66	1676	1732	CX90	2286	2342
CX44	1118	1174	CX68	1727	1783	CX95	2413	2469
CX46	1168	1224	CX70	1778	1834	CX100	2540	2596
CX48	1219	1275	CX72	1829	1885	CX120	3048	3104
CX50	1270	1326	CX74	1880	1936			
CX52	1321	1377	CX76	1930	1986			
CX54	1372	1428	CX78	1981	2037			
CX56	1422	1478	CX80	2032	2088			
CX58	1473	1529	CX82	2083	2139			
CX60	1524	1580	CX84	2134	2190			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request