


# ENDURA HI-TECH 'FLEX' WEDGE V BELTS

**TABLE 5A**

**Classical Section:SPZX**




**Top Width:** 10.0 mm; **Thickness:** 8.0 mm; **Angle:** 36°  
**Standard:** IS 14261, BS 3790, ISO 4184, DIN 7753  
**Temperature Range:** + 90°C to -18°C  
**Features:** Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
SPZX710	673	710	SPZX1112	1075	1112	SPZX1700	1663	1700	SPZX2500	2463	2500
SPZX750	713	750	SPZX1180	1143	1180	SPZX1750	1713	1750	SPZX2650	2613	2650
SPZX787	750	787	SPZX1250	1213	1250	SPZX1800	1763	1800	SPZX2800	2763	2800
SPZX800	763	800	SPZX1320	1283	1320	SPZX1850	1813	1850	SPZX3000	2963	3000
SPZX850	813	850	SPZX1400	1363	1400	SPZX1900	1863	1900			
SPZX900	863	900	SPZX1450	1413	1450	SPZX2000	1963	2000			
SPZX950	913	950	SPZX1500	1463	1500	SPZX2120	2083	2120			
SPZX1000	963	1000	SPZX1600	1563	1600	SPZX2240	2203	2240			
SPZX1100	1063	1100	SPZX1612	1575	1612	SPZX2360	2323	2360			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request  
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request

**TABLE 5B**

**Classical Section:SPAX**



**Top Width:** 13.0 mm; **Thickness:** 10.0 mm; **Angle:** 36°  
**Standard:** IS 14261, BS 3790, ISO 4184, DIN 7753  
**Temperature Range:** + 90°C to -18°C  
**Features:** Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
SPAX800	755	800	SPAX1180	1135	1180	SPAX1800	1755	1800	SPAX2650	2605	2650
SPAX850	805	850	SPAX1250	1205	1250	SPAX1900	1855	1900	SPAX2800	2755	2800
SPAX900	855	900	SPAX1320	1275	1320	SPAX1950	1905	1950	SPAX3000	2955	3000
SPAX950	905	950	SPAX1400	1355	1400	SPAX2000	1955	2000			
SPAX1000	955	1000	SPAX1500	1455	1500	SPAX2120	2075	2120			
SPAX1060	1015	1060	SPAX1557	1512	1557	SPAX2240	2195	2240			
SPAX1080	1035	1080	SPAX1600	1555	1600	SPAX2360	2315	2360			
SPAX1120	1075	1120	SPAX1700	1655	1700	SPAX2480	2435	2480			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request  
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request