


TABLE 5C

Classical Section:SPBX




Top Width: 17.0 mm; **Thickness:** 14.0 mm; **Angle:** 36°
Standard: IS 14261, BS 3790, ISO 4184, DIN 7753
Temperature Range: + 90°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
SPBX1250	1190	1250	SPBX1700	1640	1700	SPBX2360	2300	2360	SPBX3350	3290	3350
SPBX1300	1240	1300	SPBX1800	1740	1800	SPBX2410	2350	2410	SPBX3550	3490	3550
SPBX1350	1290	1350	SPBX1900	1840	1900	SPBX2500	2440	2500			
SPBX1400	1340	1400	SPBX2000	1940	2000	SPBX2650	2590	2650			
SPBX1500	1440	1500	SPBX2120	2060	2120	SPBX2800	2740	2800			
SPBX1600	1540	1600	SPBX2240	2180	2240	SPBX3000	2940	3000			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request

TABLE 5D

Classical Section:SPCX



Top Width: 22.0 mm; **Thickness:** 18.0 mm; **Angle:** 36°
Standard: IS 14261, BS 3790, ISO 4184, DIN 7753
Temperature Range: + 90°C to -18°C
Features: Antistatic, Oil and Heat Resistant

Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length	Belt Code	Inside Length	Pitch Length
SPCX2120	2037	2120	SPCX2650	2567	2650	SPCX3350	3267	3350	SPCX4150	4067	4150
SPCX2240	2157	2240	SPCX2800	2717	2800	SPCX3550	3467	3550	SPCX4250	4167	4250
SPCX2360	2277	2360	SPCX3000	2917	3000	SPCX3750	3667	3750	SPCX4500	4417	4500
SPCX2500	2417	2500	SPCX3150	3067	3150	SPCX4000	3917	4000			

Belts can be manufactured in Kevlar Cord. MOQ, Manufacturing time and rates are available on request
 Intermediate sizes can be manufactured. MOQ, Manufacturing time and rates are available on request